



## OILFLEX



Descrizione <i>Description</i>	P Es. Bar <i>Working Press. Bar</i>	Asp. mt/H <sub>2</sub> O <i>Suction m/H<sub>2</sub>O</i>	Peso gr/mt <i>Weight gr/m</i>	UM	
TUBO P OILFLEX 25	9	9	540	MT	50
TUBO P OILFLEX 30	7	9	680	MT	50
TUBO P OILFLEX 35	7	9	750	MT	50
TUBO P OILFLEX 40	7	9	850	MT	50
TUBO P OILFLEX 50	6	9	1200	MT	50
TUBO P OILFLEX 60	6	9	1700	MT	50
TUBO P OILFLEX 80	5	9	2200	MT	30
TUBO P OILFLEX 100	4	9	3300	MT	30

I VALORI RIPORTATI SONO RIFERITI AD UNA TEMPERATURA DI +18°C | THE DATA ARE REFERRED TO A TEMPERATURE OF +18°C

### IT|

Tubo in PVC flessibile colore azzurro con spirale in PVC rigido antiurto colore bianco. Impiego: mandata ed aspirazione di gasolio ed oli combustibili. Raggio di curvatura: 6 volte il diametro interno. Temperatura impiego: -10°C +60°C. Su richiesta viene realizzato in versione antistatica (con cavetto di rame inserito).

### EN|

PVC hose, blue color, flexible, with white crash proof PVC spiral, designed to handle diesel oil and heating oil. Bending radius 6 times the inside diameter. Temperature range: -10°C to +60°C. On request, with antistatic copper wire built in the hose wall for earthing.

Le informazioni contenute in questa scheda sono basate sulle nostre conoscenze ed esperienze attuali. Non possono comunque implicare una garanzia né una responsabilità da parte nostra circa l'utilizzo dei nostri prodotti, non essendo le condizioni di impiego sotto il nostro controllo. Salvo errori tipografici. È vietata la riproduzione anche parziale di questa scheda.

We have made every effort to ensure that details and information given in this data sheet are accurate at the time of issue but give no guarantees as to the accuracy or completeness of such information nor liability by our part regarding the use of the products. No part of this publication may be reproduced or transmitted in any form or by any means including photocopying and recording, without our written permission.

